



# BLO01000 Marine Engine Oil 2-Stroke Detroit Diesel SAE 40

Document version: February 7th 2019



## Description

The engine oil 2-Stroke Detroit Diesel SAE 40 is developed for use in 2-stroke Detroit Diesel engines which operating under severe conditions with a limit sulphated ash specification of 0.8%.

This type of oil is not recommended when using fuel with a sulfur content higher than 0.5%.

This oil is used in 2-stroke Detroit Diesel Series 53, 71, 92 and 149 in the shipping, the industry and road traffic.

## According to the specifications of

API CD-II / CF / CF-2  
Detroit Diesel 7SE270

## Packing units

ART. NO.	VOLUME	ITEMS PER UNIT	ITEMS PER PALLET
BLO01005	5 L	4	112
BLO01020	20 L	1	30
BLO01060	60 L	1	12
BLO01205	205 L	1	2
BLO01999	1000 L	1	-

## Typical characteristics

TEST	VALUE	
SAE	40	
Density at 15°C	0,897	kg/l
Kinematic viscosity at 40°C	138	mm <sup>2</sup> /s
Kinematic viscosity at 100°C	14,0	mm <sup>2</sup> /s
Viscosity index	98	
Flashpoint COC	225	°C
Pourpoint	-15	°C
Total Base number	5,9	mgKOH/g
Sulphated ash	0,8	mass%