



03000D Motor Oil 15W-40 Super High Performance Diesel

Document version: November 18th 2018



Description

This high grade mineral motor oil has been specially developed for heavy duty diesel engines with or without turbochargers. In addition, this motor oil has been formulated to make extended oil-change intervals possible and to prevent bore polishing.

According to the specifications of

ACEA A3/B4 / E3 / E5 / E7
Allison C4
API CF / CF-4 / CG-4 / CH-4 / CI-4 / SL
Caterpillar ECF-1a / ECF-2
Cummins CES 20076 / CES 20077 / CES 20078
Detroit Diesel 93K215
Deutz DQC III-10
Global DHD-1
JASO DH-1
Mack EO-M Plus / EO-N
MAN M 3275
MB-Approval 228.3 / 229.1
MTU Type 2
Renault RLD / RLD-2
Volvo VDS-3

Packing units

ART. NO.	VOLUME	ITEMS PER UNIT	ITEMS PER PALLET
03001D	1 L	6	450
03005D	5 L	4	112
03020D	20 L	1	30
03060D	60 L	1	12
03205D	205 L	1	2
03999D	1000 L	1	-
P03000D	bulk	1	-

Typical characteristics

TEST	VALUE	
Density at 15°C	0,888	kg/l
Kinematic viscosity at 40°C	100.0	mm ² /s
Kinematic viscosity at 100°C	14.0	mm ² /s
Viscosity index	135	
Dynamic viscosity at -20°C	6500	mPa·s
Flashpoint COC	220	°C
Pourpoint	-36	°C
Total Base number	10.7	mgKOH/g
Sulphated ash	1.34	mass%