



05000DX1 Motor Oil 5W-30 Premium Synthetic DX1

Document version: November 18th 2018



Description

This MPM premium synthetic motor oil is specially formulated to meet the latest requirements for petrol engines of passenger cars, light commercial vehicles and SUVs.

Developed for better low speed pre-ignition (LSPI) protection, particularly for Opel / GM small displacement turbo charged engines.

This fully synthetic engine oil offers total engine protection and keeps the engine clean even under the most severe conditions.

Due the excellent thin-flowability this engine oil offers excellent cold start properties.

According to the specifications of

API SN Plus / SN-RC

Chrysler MS-6395

Ford WSS-M2C945-A / WSS-M2C946-A

ILSAC GF-5

Opel/GM dexos1™ Gen 2

Packing units

ART. NO.	VOLUME	ITEMS PER UNIT	ITEMS PER PALLET
05001DX1	1 L	6	-
05005DX1	5 L	4	-
05020DX1	20 L	1	-
05060DX1	60 L	1	-
05205DX1	205 L	1	-
05999DX1	1000 L	1	-
P05000DX1	bulk	1	-

Typical characteristics

TEST	METHOD	VALUE	
SAE		5W-30	
Density at 15°C	ASTM D4052	0.853	kg/l
Kinematic viscosity at 40°C	ASTM D445	60.9	mm ² /s
Kinematic viscosity at 100°C	ASTM D445	10.4	mm ² /s
Viscosity index	ASTM D2270	159	
Flashpoint COC	ASTM D92	221	°C
Pourpoint	ASTM D7346	-45	°C
Total Base number	ASTM D2896	9.2	mgKOH/g
Sulphated ash	ASTM D874	0.94	mass%