



05000PC Motor Oil 0W-30 Premium Synthetic PC

Document version: November 18th 2018



Description

This fully synthetic 'low SAPS' engine oil is designed for gasoline and diesel engines equipped with an exhaust after-treatment system. Highly suitable for extended drain intervals, taking into account the use of bio-components in the fuel. Excellent viscosity at low temperatures in combination with stop / start technology provides 4.2% fuel saving in comparison to a 5W-40 reference oil. This engine oil is mandatory for PSA Euro VI Blue DW10F HDi engines.

According to the specifications of

ACEA C2
PSA B71 2312

Packing units

ART. NO.	VOLUME	ITEMS PER UNIT	ITEMS PER PALLET
05001PC	1 L	6	450
05005PC	5 L	4	112
05020PC	20 L	1	30
05060PC	60 L	1	12
05205PC	205 L	1	2
05999PC	1000 L	1	-
P05000PC	bulk	1	-

Typical characteristics

TEST	METHOD	VALUE	
Density at 15°C	ASTM D4052	0,842	kg/l
Kinematic viscosity at 40°C	ASTM D445	52,0	mm ² /s
Kinematic viscosity at 100°C	ASTM D445	9,6	mm ² /s
Viscosity index	ASTM D92	172	
Dynamic viscosity at -35°C	ASTM D97	5850	mPa·s
Flashpoint COC	ASTM D2986	230	°C
Pourpoint	ASTM D874	-48	°C
Total Base number		6,2	mgKOH/g
Sulphated ash		0,56	mass%