



06000PS Motor Oil 0W-40 Pro Street C3

Document version: November 18th 2018



Description

This premium synthetic fuel economy 'MID SAPS' engine oil has been specially developed for petrol and diesel engines with or without a turbocharger. Due to its good thermal and oxidation stability together with excellent protection against wear and corrosion, it offers optimum engine protection. This MPM Motor Oil 0W-40 Pro Street C3 is suitable for passenger cars and light commercial vehicles equipped with an exhaust after-treatment system.

According to the specifications of

ACEA C3
API CF / SN

Packing units

ART. NO.	VOLUME	ITEMS PER UNIT	ITEMS PER PALLET
06001PS	1 L	6	450
06020PS	20 L	1	30
06060PS	60 L	1	12
06205PS	205 L	1	2
P06000PS	bulk	1	-

Typical characteristics

TEST	METHOD	VALUE	
SAE		0W-40	
Density at 15°C	ASTM D4052	0.856	kg/l
Kinematic viscosity at 40°C	ASTM D445	75.8	mm ² /s
Kinematic viscosity at 100°C	ASTM D445	13.6	mm ² /s
Viscosity index	ASTM D2270	185	
Dynamic viscosity at -30°C	ASTM D5293	6600	mPa·s
Flashpoint COC	ASTM D92	218	°C
Pourpoint	ASTM D97	-42	°C
Total Base number	ASTM D2986	7.5	mgKOH/g
Sulphated ash	ASTM D874	0.79	mass%