



# 06000S Motor Oil 0W-40 High Performance Street

Document version: November 18th 2018



## Description

This premium synthetic high-grade motor oil has been specially developed for the latest generation of high performance engine performance. This motor oil ensures excellent protection against wear at high revolutions due to a superior lubrication film.

## According to the specifications of

ACEA A3/B4  
API SN  
BMW LL-01  
ILSAC GF-4  
MB-Approval 229.5  
Porsche A40  
Renault RN 0700 / RN 0710  
VW 502.00 / 505.00

## Packing units

ART. NO.	VOLUME	ITEMS PER UNIT	ITEMS PER PALLET
06001S	1 L	6	450
06005S	5 L	4	112
06020S	20 L	1	30
06060S	60 L	1	12
06205S	205 L	1	2
06999S	1000 L	1	-
P06000S	bulk	1	-

## Typical characteristics

TEST	METHOD	VALUE	
Density at 15°C	ASTM D4052	0.844	kg/l
Kinematic viscosity at 40°C	ASTM D445	80.1	mm <sup>2</sup> /s
Kinematic viscosity at 100°C	ASTM D445	13.8	mm <sup>2</sup> /s
Viscosity index	ASTM D2270	178	
Dynamic viscosity at -35°C	ASTM D5293	6040	mPa·s
Flashpoint COC	ASTM D92	220	°C
Pourpoint	ASTM D6892	-57	°C
Total Base number	ASTM D2896	10.1	mgKOH/g
Sulphated ash	ASTM D874	1.09	mass%