



05000DPF Motor Oil 5W-30 Premium Synthetic C3 DPF

Document version: Aug 26, 2020



Description

This premium synthetic motor oil has been specially developed for BMW and Mercedes-Benz engines. This motor oil has the approvals of BMW Long Life 04 and Mercedes-Benz Long Life 229.51 / 229.52.. This SAE 5W-30 motor oil with ACEA C3 standard is recommended for petrol and diesel engines fitted with exhaust gas after-treatment systems.

According to the specifications of

ACEA C3
API CF / SN
BMW LL-04<2019
MB-Approval 229.51 / 229.52
Opel/GM dexos2™
VW 502.00 / 505.00 / 505.01

Packaging units

ART. NR.	VOLUME	ITEMS PER UNIT	ITEMS PER PALLET
05001DPF	1 L	6	450
05005DPF	5 L	4	112
05020DPF	20 L	1	30
05060DPF	60 L	1	12
05205DPF	205 L	1	2
05999DPF	1000 L	1	-
P05000DPF	1 L	1	-

TEST	VALUE	
Viscosity	5W-30	
Density at 15°C	0.855	kg/l
Kinematic Viscosity at 40°C	74.3	mm ² /s
Kinematic Viscosity at 100°C	12.4	mm ² /s
Viscosity Index	166	
Dynamic Viscosity at -30°C	6060	mPa.s
Flashpoint COC	230	°C
Pourpoint	-39	°C
Total Base Number	7.6	mgKOH/g
Sulphated Ash	0.8	mass%
High Temperature High Share	0	mPa.s
Noack Evaporation Loss	0	mass%

These characteristics are typical of current production. Variations in these characteristics may occur.