



Motor Oil 10W-40 Super High Performance Diesel Truck

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Date of issue:

Revision date: 14/04/2014

version: 6.5

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name : Motor Oil 10W-40 Super High Performance Diesel Truck

Product code : 04000A

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category : Industrial use, Professional use, Consumer use

Use of the substance/mixture : Automotive care products

Function or use category : Lubricants and additives

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

MPM International Oil Company
Cyclotronweg 1
2629 HN Delft - Nederland
T +31 (0)15 2514030 - F +31 (0)15 2514031
info@mpmoil.nl - www.mpmoil.nl

1.4. Emergency telephone number

Emergency number : +31 (0)15 2514030 (08.00 - 17.00)

Country	Official advisory body	Address	Emergency number
Ireland	National Poisons Information Centre Beaumont Hospital	Beaumont Hospital Beaumont Road 9 Dublin	: +353 1 8379964
United Kingdom	Guy's & St Thomas' Poisons Unit Medical Toxicology Unit, Centre Hospitalier Universitaire de Constantine	Avonley Road SE14 5ER London	0870 243 2241

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Not classified

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

EUH-statements : EUH210 - Safety data sheet available on request

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Polyolefine polyamine succinimide, polyol	(CAS No) 147880-09-9	1 - 5	Aquatic Chronic 4, H413
Zinc Alkyldithiophosphate	(CAS No) 68649-42-3 (EC no) 272-028-3 (REACH-no) 01-2119493635-27	0,5 - 1,5	Skin Irrit. 2, H315 Eye Dam. 1, H318 Aquatic Chronic 2, H411

Motor Oil 10W-40 Super High Performance Diesel Truck

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Calcium long chain alkaryl sulphonate	(CAS No) 90194-27-7 (EC no) 290-636-7 (EC index no) 271-877-7	0,1 - 0,99	Skin Sens. 1, H317 Aquatic Chronic 4, H413
---------------------------------------	---	------------	---

Specific concentration limits:

Name	Product identifier	Specific concentration limits
Zinc Alkyldithiophosphate	(CAS No) 68649-42-3 (EC no) 272-028-3 (REACH-no) 01-2119493635-27	(5 =<C < 10) Eye Irrit. 2, H319 (C >= 10) Eye Dam. 1, H318

Full text of H-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

After inhalation	: No special measures are necessary.
After skin contact	: Wash with plenty of soap and water.
After eye contact	: In case of contact with eyes, rinse immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart.
After ingestion	: Do NOT induce vomiting. Rinse mouth. Get immediate medical advice/attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries	: Not expected to present a significant hazard under anticipated conditions of normal use.
-------------------	--

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: hazy water, powder, foam and CO ₂ .
Unsuitable extinguishing media	: High power water jet.

5.2. Special hazards arising from the substance or mixture

No additional information available

5.3. Advice for firefighters

Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection.
Other information	: Exercise caution when fighting any chemical fire. Use water spray/stream to protect personnel and to cool endangered containers.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Protective equipment	: Wear suitable protective clothing and gloves.
----------------------	---

6.1.2. For emergency responders

Protective equipment	: Wear suitable protective clothing and gloves.
----------------------	---

6.2. Environmental precautions

Do not release in groundwater, surfacewater or sewerage. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

For containment	: Prevent spreading over great surfaces (e.g. by damming or installing oil booms).
Methods for cleaning up	: Clean with the help of detergents. Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents).
Other information	: Can be slippery on hard, smooth walking area.

6.4. Reference to other sections

No additional information available

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling	: Avoid all unnecessary exposure. Both local exhaust and general room ventilation are usually required.
Handling temperature	: < 40 °C
Hygiene measures	: Wash hands before breaks and at the end of work. When using do not eat, drink or smoke.

7.2. Conditions for safe storage, including any incompatibilities

Storage temperature	: < 40 °C
Storage area	: Keep container tightly closed in a cool, well-ventilated place.

Motor Oil 10W-40 Super High Performance Diesel Truck

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Additional information : Based on ACGIH TLV, a concentration of 5 mg/m³ oilspray (TWA, 8 hour workday) is recommended.

8.2. Exposure controls

Hand protection : Wear suitable gloves resistant to chemical penetration
Eye protection : Safety glasses
Skin and body protection : No special clothing/skin protection equipment is recommended under normal conditions of use
Respiratory protection : No special respiratory protection equipment is recommended under normal conditions of use with adequate ventilation

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid
Appearance : Oily.
Colour : Yellowbrown.
Odour : characteristic.
Odour threshold : No data available
pH : No data available
Relative evaporation rate (butylacetate=1) : No data available
Melting point : No data available
Freezing point : No data available
Boiling point : No data available
Flash point : > 200 °C ASTM D 92
Auto-ignition temperature : No data available
Decomposition temperature : No data available
Flammability (solid, gas) : No data available
Vapour pressure : No data available
Relative vapour density at 20 °C : No data available
Relative density : No data available
Density : 872 g/l @ 15°C
Solubility : Slightly soluble, the product remains on the water surface.
Log Pow : No data available
Viscosity, kinematic : 87 mm²/s @ 40°C
Viscosity, dynamic : No data available
Explosive properties : No data available
Oxidising properties : No data available
Explosive limits : No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

None under normal conditions.

10.2. Chemical stability

The product is stable at normal handling- and storage conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

No additional information available

10.5. Incompatible materials

Strong oxidizing agent. Acids and bases.

Motor Oil 10W-40 Super High Performance Diesel Truck

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

10.6. Hazardous decomposition products

None under normal conditions.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

Zinc Alkyldithiophosphate (68649-42-3)	
LD50 oral rat	2230 mg/kg
LD50 dermal rat	> 2000 mg/kg
Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
Specific target organ toxicity (single exposure)	: Not classified
Specific target organ toxicity (repeated exposure)	: Not classified
Aspiration hazard	: Not classified

Motor Oil 10W-40 Super High Performance Diesel Truck	
Viscosity, kinematic	87 mm ² /s @ 40°C

SECTION 12: Ecological information

12.1. Toxicity

Polyolefine polyamine succinimide, polyol (147880-09-9)	
LC50 fish 1	No data available
Zinc Alkyldithiophosphate (68649-42-3)	
LC50 fish 1	1 - 5 mg/l @ 96h
EC50 Daphnia 1	1 - 1,5 @ 48 h
EC50 other aquatic organisms 2	1 - 5 mg/l Algae @ 96 h
NOEC (acute)	1 mg/l @ 96 h (Fish)
NOEC chronic algae	1 mg/l @ 96 h
Calcium long chain alkaryl sulphonate (90194-27-7)	
LC50 fish 1	No data available

12.2. Persistence and degradability

Zinc Alkyldithiophosphate (68649-42-3)	
Persistence and degradability	No data available.
Calcium long chain alkaryl sulphonate (90194-27-7)	
Persistence and degradability	Not soluble in water, so only minimally biodegradable.

12.3. Bioaccumulative potential

Zinc Alkyldithiophosphate (68649-42-3)	
Bioaccumulative potential	not determined.
Calcium long chain alkaryl sulphonate (90194-27-7)	
Log Kow	> 3
Bioaccumulative potential	No additional information available.

12.4. Mobility in soil

Zinc Alkyldithiophosphate (68649-42-3)	
Soil	No data available.
Calcium long chain alkaryl sulphonate (90194-27-7)	
Soil	No data available.

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Other adverse effects

No additional information available

Motor Oil 10W-40 Super High Performance Diesel Truck

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Regional legislation (waste) : Waste disposal according to official state regulations.
Waste disposal recommendations : Remove to an authorized waste treatment plant.

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

14.1. UN number

Not regulated for transport

14.2. UN proper shipping name

Proper Shipping Name (ADR) : Not applicable
Proper Shipping Name (IMDG) : Not applicable

14.3. Transport hazard class(es)

ADR

Transport hazard class(es) (ADR) : Not applicable

IMDG

Transport hazard class(es) (IMDG) : Not applicable

14.4. Packing group

Packing group (ADR) : Not applicable
Packing group (IMDG) : Not applicable

14.5. Environmental hazards

Dangerous for the environment : No
Marine pollutant : No
Other information : No supplementary information available

14.6. Special precautions for user

- Overland transport

No data available

- Transport by sea

No data available

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions
Contains no substance on the REACH candidate list
Contains no REACH Annex XIV substances

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No additional information available

SECTION 16: Other information

Full text of H- and EUH-statements:

Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Aquatic Chronic 4	Hazardous to the aquatic environment — Chronic Hazard, Category 4
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Sensitisation — Skin, Category 1

Motor Oil 10W-40 Super High Performance Diesel Truck

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H411	Toxic to aquatic life with long lasting effects.
H413	May cause long lasting harmful effects to aquatic life.
EUH210	Safety data sheet available on request.

SDS MPM REACH

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product