



# Motor Oil 10W-40 Premium Synthetic Ultra High Performance Diesel

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Revision date: 25-1-2018 Supersedes: 20-2-2015 version: 8.0

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Mixture  
 Product name : Motor Oil 10W-40 Premium Synthetic Ultra High Performance Diesel  
 Product code : 05000AB

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### 1.2.1. Relevant identified uses

Main use category : Industrial use, Professional use, Consumer use  
 Use of the substance/mixture : Automotive care products  
 Function or use category : Lubricants and additives

##### 1.2.2. Uses advised against

No additional information available

#### 1.3. Details of the supplier of the safety data sheet

MPM International Oil Company  
 Cyclotronweg 1  
 2629 HN Delft - Nederland  
 T +31 (0)15 2514030 - F +31 (0)15 2514031  
[info@mpmoil.nl](mailto:info@mpmoil.nl) - [www.mpmoil.nl](http://www.mpmoil.nl)

#### 1.4. Emergency telephone number

Emergency number : +31 (0)15 2514030 (08.00 - 17.00 GMT+1)

Country	Official advisory body	Address	Emergency number	Comment
Ireland	National Poisons Information Centre Beaumont Hospital	Beaumont Hospital Beaumont Road 9 Dublin	: +353 1 8379964	
United Kingdom	Guy's & St Thomas' Poisons Unit Medical Toxicology Unit, Guy's & St Thomas' Hospital Trust	Avonley Road SE14 5ER London	0870 243 2241	

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Not classified

##### Adverse physicochemical, human health and environmental effects

No additional information available

#### 2.2. Label elements

##### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

EUH-statements : EUH210 - Safety data sheet available on request.  
 EUH208 - Contains C14-16-18 Alkylphenol, Molybdeenpolysulfide-alkyldithiocarbamaatlongchaincomplex. May produce an allergic reaction.

#### 2.3. Other hazards

No additional information available

### SECTION 3: Composition/information on ingredients

#### 3.1. Substances

Not applicable

#### 3.2. Mixtures

# Motor Oil 10W-40 Premium Synthetic Ultra High Performance Diesel

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Reaction products of benzeneamine, N-phenyl- with nonene (branched)	(CAS-No.) 36878-20-3 (EC-No.) 253-249-4 (REACH-no) 01-2119488911-28	1 - 4,99	Aquatic Chronic 4, H413
Distillates (petroleum), solvent-dewaxed heavy paraffinic, Baseoil - unspecified, [A complex combination of hydrocarbons obtained by removal of normal paraffins from a petroleum fraction by solvent crystallization. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity not less than 100 SUS at 100 °F (19cSt at 40 °C).]	(CAS-No.) 64742-65-0 (EC-No.) 265-169-7 (EC Index-No.) 649-474-00-6	1 - 4,99	Asp. Tox. 1, H304
Zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)]bis(dithiophosphate)	(CAS-No.) 93819-94-4 (EC-No.) 298-577-9 (REACH-no) 01-2119543726-33	0,1 - 0,99	Skin Irrit. 2, H315 Eye Dam. 1, H318 Aquatic Chronic 2, H411
C14-16-18 Alkylphenol	(REACH-no) 01-2119498288-19	0,1 - 0,99	Skin Sens. 1, H317 STOT RE 2, H373
Molybdeenpolysulfide-alkyldithiocarbamaatlongchaincomplex	(EC-No.) 457-320-2 (REACH-no) 01-0000019337-66	0,1 - 0,99	Skin Irrit. 2, H315 Skin Sens. 1, H317 Aquatic Chronic 3, H412

### Specific concentration limits:

Name	Product identifier	Specific concentration limits
Zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)]bis(dithiophosphate)	(CAS-No.) 93819-94-4 (EC-No.) 298-577-9 (REACH-no) 01-2119543726-33	( 6,25 =<C < 100) Skin Irrit. 2, H315 ( 10 =<C < 12,5) Eye Irrit. 2, H319 ( 12,5 =<C < 100) Eye Dam. 1, H318

Full text of H-statements: see section 16

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

After inhalation	: No special measures are necessary.
After skin contact	: Wash with plenty of soap and water.
After eye contact	: In case of contact with eyes, rinse immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart.
After ingestion	: Do NOT induce vomiting. Rinse mouth. Get immediate medical advice/attention.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects	: Not expected to present a significant hazard under anticipated conditions of normal use.
------------------	--

### 4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media	: water spray, powder, foam and CO2.
Unsuitable extinguishing media	: High power water jet.

### 5.2. Special hazards arising from the substance or mixture

No additional information available

### 5.3. Advice for firefighters

Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection.
Other information	: Exercise caution when fighting any chemical fire. Use water spray/stream to protect personnel and to cool endangered containers.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

#### 6.1.1. For non-emergency personnel

Protective equipment	: Wear suitable protective clothing and gloves.
----------------------	---

#### 6.1.2. For emergency responders

Protective equipment	: Wear suitable protective clothing and gloves.
----------------------	---

### 6.2. Environmental precautions

Do not release in groundwater, surfacewater or sewerage. Notify authorities if liquid enters sewers or public waters.

# Motor Oil 10W-40 Premium Synthetic Ultra High Performance Diesel

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### 6.3. Methods and material for containment and cleaning up

- For containment : Prevent spreading over great surfaces (e.g. by damming or installing oil booms).  
Methods for cleaning up : Clean with the help of detergents. Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents).  
Other information : Can be slippery on hard, smooth walking area.

### 6.4. Reference to other sections

No additional information available

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

- Precautions for safe handling : Avoid all unnecessary exposure. Both local exhaust and general room ventilation are usually required.  
Handling temperature : < 40 °C  
Hygiene measures : When using do not eat, drink or smoke. Wash hands before breaks and at the end of work.

### 7.2. Conditions for safe storage, including any incompatibilities

- Storage temperature : < 40 °C  
Storage area : Keep container tightly closed in a cool, well-ventilated place.

### 7.3. Specific end use(s)

No additional information available

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

Molybdeenpolysulfide-alkyldithiocarbamaatlongchaincomplex		
EU	IOELV TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup>

- Additional information : Based on ACGIH TLV, a concentration of 5 mg/m<sup>3</sup> oilspray (TWA, 8 hour workday) is recommended.

### 8.2. Exposure controls

#### Hand protection:

Wear suitable gloves resistant to chemical penetration

Type	Material	Permeation	Thickness (mm)	Penetration	Standard
Reusable gloves	Nitrile rubber (NBR), Polyvinylchloride (PVC)	5 (> 240 minutes)			

#### Eye protection:

Safety glasses

#### Skin and body protection:

No special clothing/skin protection equipment is recommended under normal conditions of use

#### Respiratory protection:

No special respiratory protection equipment is recommended under normal conditions of use with adequate ventilation

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

- Physical state : Liquid  
Appearance : Oily.  
Colour : Yellowbrown.  
Odour : characteristic.  
Odour threshold : No data available  
pH : No data available  
Relative evaporation rate (butylacetate=1) : No data available  
Melting point : No data available  
Freezing point : No data available  
Boiling point : No data available  
Flash point : > 200 °C ASTM D 92

# Motor Oil 10W-40 Premium Synthetic Ultra High Performance Diesel

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Density	: 859 g/l @ 15°C
Solubility	: Slightly soluble, the product remains on the water surface.
Log Pow	: No data available
Viscosity, kinematic	: 88 mm <sup>2</sup> /s @ 40°C
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

### 9.2. Other information

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

None under normal conditions.

### 10.2. Chemical stability

The product is stable at normal handling- and storage conditions.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4. Conditions to avoid

No additional information available

### 10.5. Incompatible materials

Strong oxidizing agent. Acids and bases.

### 10.6. Hazardous decomposition products

None under normal conditions.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity : Not classified

#### Reaction products of benzeneamine, N-phenyl- with nonene (branched) (36878-20-3)

LD50 oral rat	> 5000 mg/kg (OECD 401 method)
LD50 dermal rat	> 2000 mg/kg (OECD 402 method)

**Distillates (petroleum), solvent-dewaxed heavy paraffinic, Baseoil - unspecified, [A complex combination of hydrocarbons obtained by removal of normal paraffins from a petroleum fraction by solvent crystallization. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity not less than 100 SUS at 100 °F (19cSt at 40 °C).] (64742-65-0)**

LD50 oral	> 5000 mg/kg
LD50 dermal rabbit	> 5000 mg/kg
LC50 inhalation rat (mg/l)	5,53 mg/l/4h

#### Zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)]bis(dithiophosphate) (93819-94-4)

LD50 oral rat	2600 mg/kg
LD50 dermal rat	> 3160 mg/kg OECD 402

Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified

# Motor Oil 10W-40 Premium Synthetic Ultra High Performance Diesel

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

<b>Distillates (petroleum), solvent-dewaxed heavy paraffinic, Baseoil - unspecified, [A complex combination of hydrocarbons obtained by removal of normal paraffins from a petroleum fraction by solvent crystallization. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity not less than 100 SUS at 100 °F (19cSt at 40 °C).] (64742-65-0)</b>	
LOAEL (oral, rat, 90 days)	125 mg/kg bodyweight/day
NOAEC (inhalation, rat, dust/mist/fume, 90 days)	> 980 mg/l/6h/day
NOAEL (subchronic, oral, animal/male, 90 days)	>= 2000 mg/kg bodyweight
NOAEL (subchronic, oral, animal/female, 90 days)	>= 2000 mg/kg bodyweight

Aspiration hazard : Not classified

<b>Motor Oil 10W-40 Premium Synthetic Ultra High Performance Diesel</b>	
Viscosity, kinematic	88 mm <sup>2</sup> /s @ 40°C

## SECTION 12: Ecological information

### 12.1. Toxicity

<b>Reaction products of benzeneamine, N-phenyl- with nonene (branched) (36878-20-3)</b>	
LC50 fish 1	> 100 mg/l @ 96h
LC50 other aquatic organisms 1	600 mg/l @ 72h (Algae)
EC50 Daphnia 1	51 mg/l @ 48h
EC50 72h algae (1)	> 100 mg/l
NOEC chronic algae	33 mg/l @ 96h
<b>Zinc bis[O-(-6-methylheptyl)] bis[O-(sec-butyl)]bis(dithiophosphate) (93819-94-4)</b>	
LC50 fish 1	4,5 ml/l OECD 203 (oncorhynchys mykiss, 96h)
EC50 Daphnia 1	5,4 mg/l OECD 202, (Daphnia magna, 72h)
EC50 other aquatic organisms 1	2,1 ml/l OECD 201 (Selenastrum capricornutum , 48h)
<b>Molybdeenpolysulfide-alkyldithiocarbamaatlongchaincomplex</b>	
EC50 Daphnia 1	50 mg/l OECD 202
EC50 72h algae (1)	9,62 mg/l OECD 201.
NOEC (acute)	94,8 mg/l
NOEC chronic algae	100 mg/l @21d Daphnia Magna

### 12.2. Persistence and degradability

<b>Reaction products of benzeneamine, N-phenyl- with nonene (branched) (36878-20-3)</b>	
Persistence and degradability	Poorly biodegradable.
Biodegradation	0 % Sturm-test @28d
<b>Zinc bis[O-(-6-methylheptyl)] bis[O-(sec-butyl)]bis(dithiophosphate) (93819-94-4)</b>	
Biodegradation	1,5 % OECD 301B 28d
<b>Molybdeenpolysulfide-alkyldithiocarbamaatlongchaincomplex</b>	
Persistence and degradability	Not readily biodegradable.
Biodegradation	22,75 % 29d

### 12.3. Bioaccumulative potential

<b>Reaction products of benzeneamine, N-phenyl- with nonene (branched) (36878-20-3)</b>	
Bioconcentration factor (BCF REACH)	1730
Log Kow	3,6 @0.1d
Bioaccumulative potential	Moderate bioconcentration.
<b>Distillates (petroleum), solvent-dewaxed heavy paraffinic, Baseoil - unspecified, [A complex combination of hydrocarbons obtained by removal of normal paraffins from a petroleum fraction by solvent crystallization. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity not less than 100 SUS at 100 °F (19cSt at 40 °C).] (64742-65-0)</b>	
Log Pow	> 3
<b>Zinc bis[O-(-6-methylheptyl)] bis[O-(sec-butyl)]bis(dithiophosphate) (93819-94-4)</b>	
Log Pow	0,9 @ 23C
<b>Molybdeenpolysulfide-alkyldithiocarbamaatlongchaincomplex</b>	
BCF fish 1	88 OECD 305 (Cyprinus carpio, 25C)
Bioconcentration factor (BCF REACH)	88 OECD 305 (Cyprinus carpio, 25C - 0.05mg/l)

# Motor Oil 10W-40 Premium Synthetic Ultra High Performance Diesel

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### 12.4. Mobility in soil

#### Reaction products of benzeneamine, N-phenyl- with nonene (branched) (36878-20-3)

Log Koc	> 2000
---------	--------

Soil	Low mobility (soil).
------	----------------------

#### Molybdeenpolysulfide-alkyldithiocarbamaatlongchaincomplex

Soil	Adsorbs into the soil.
------	------------------------

### 12.5. Results of PBT and vPvB assessment

#### Component

Reaction products of benzeneamine, N-phenyl- with nonene (branched) (36878-20-3)	This substance does not meet the PBT/vPvB criteria of REACH, annex XIII.
--	--

### 12.6. Other adverse effects

No additional information available

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Regional legislation (waste) : Waste disposal according to official state regulations.

Waste disposal recommendations : Remove to an authorized waste treatment plant.

## SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

ADR	IMDG
<b>14.1. UN number</b>	
Not applicable	Not applicable
<b>14.2. UN proper shipping name</b>	
Not applicable	Not applicable
<b>14.3. Transport hazard class(es)</b>	
Not applicable	Not applicable
Not applicable	Not applicable
<b>14.4. Packing group</b>	
Not applicable	Not applicable
<b>14.5. Environmental hazards</b>	
Dangerous for the environment : No	Dangerous for the environment : No Marine pollutant : No
No supplementary information available	

### 14.6. Special precautions for user

#### - Overland transport

No data available

#### - Transport by sea

No data available

### 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

#### 15.1.2. National regulations

No additional information available

### 15.2. Chemical safety assessment

No additional information available

## SECTION 16: Other information

# Motor Oil 10W-40 Premium Synthetic Ultra High Performance Diesel

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Full text of H- and EUH-statements:

Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment — Chronic Hazard, Category 3
Aquatic Chronic 4	Hazardous to the aquatic environment — Chronic Hazard, Category 4
Asp. Tox. 1	Aspiration hazard, Category 1
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
STOT RE 2	Specific target organ toxicity — Repeated exposure, Category 2
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
H413	May cause long lasting harmful effects to aquatic life.
EUH208	Contains C14-16-18 Alkylphenol, Molybdeenpolysulfide-alkyldithiocarbamaatlongchaincomplex. May produce an allergic reaction.
EUH210	Safety data sheet available on request.

SDS MPM REACH

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product*