



Motor Oil 10W-40 Premium Longdrain Plus

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Revision date: 11-1-2016 version: 3.4

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
 Product name : Motor Oil 10W-40 Premium Longdrain Plus
 Product code : 05000AD
 Product group : Blend

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category : Professional use, Industrial use, Consumer use
 Use of the substance/mixture : Automotive care products
 Function or use category : Lubricants and additives

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

MPM International Oil Company
 Cyclotronweg 1
 2629 HN Delft - Nederland
 T +31 (0)15 2514030 - F +31 (0)15 2514031
info@mpmoil.nl - www.mpmoil.nl

1.4. Emergency telephone number

Emergency number : +31 (0)15 2514030 (08.00 - 17.00)

Country	Official advisory body	Address	Emergency number	Comment
Ireland	National Poisons Information Centre Beaumont Hospital	Beaumont Hospital Beaumont Road 9 Dublin	: +353 1 8379964	
United Kingdom	Guy's & St Thomas' Poisons Unit Medical Toxicology Unit, Guy's & St Thomas' Hospital Trust	Avonley Road SE14 5ER London	0870 243 2241	

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Not classified

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

EUH-statements : EUH208 - Contains C14-16-18 Alkylphenol. May produce an allergic reaction.
 EUH210 - Safety data sheet available on request.

2.3. Other hazards

Other hazards not contributing to the classification : During use in engines, contamination of oil with low levels of cancer-causing combustion products occurs. Used motor oils have been shown to cause skin cancer in mice following repeated application and continuous exposure. Brief or intermittent skin contact with used motor oil is not expected to have serious effects in humans if the oil is thoroughly removed by washing with soap and water. Avoid prolonged contact with used motor oil.

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

Motor Oil 10W-40 Premium Longdrain Plus

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	(CAS No) 72623-87-1 (EC No) 276-738-4 (EC Index No) 649-483-00-5 (REACH-no) 01-2119474889-13	10 - 30	Asp. Tox. 1, H304
Distillates (petroleum), solvent-dewaxed heavy paraffinic, Baseoil - unspecified, [A complex combination of hydrocarbons obtained by removal of normal paraffins from a petroleum fraction by solvent crystallization. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity not less than 100 SUS at 100 °F (19cSt at 40 °C).]	(CAS No) 64742-65-0 (EC No) 265-169-7 (EC Index No) 649-474-00-6 (REACH-no) 01-2119471299-27	1 - 4,99	Asp. Tox. 1, H304
Reaction products of benzeneamine, N-phenyl- with nonene (branched)	(CAS No) 36878-20-3 (EC No) 253-249-4 (REACH-no) 01-2119488911-28	1 - 2,49	Aquatic Chronic 4, H413
reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate	(CAS No) 125643-61-0 (EC No) 406-040-9 (EC Index No) 607-530-00-7	1 - 2,49	Aquatic Chronic 4, H413
Zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate)	(EC No) 298-577-9 (EC Index No) 272-028-3 (REACH-no) 01-21419543726-33	1 - 2,49	Skin Irrit. 2, H315 Eye Dam. 1, H318 Aquatic Chronic 2, H411
C14-16-18 Alkylphenol	(REACH-no) 01-2119498288-19	0,1 - 0,25	Skin Sens. 1, H317 Aquatic Chronic 4, H413

Specific concentration limits:

Name	Product identifier	Specific concentration limits
Zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate)	(EC No) 298-577-9 (EC Index No) 272-028-3 (REACH-no) 01-21419543726-33	(6,25 =<C < 100) Skin Irrit. 2, H315 (10 =<C < 12,5) Eye Irrit. 2, H319 (12,5 =<C < 100) Eye Dam. 1, H318

Full text of H-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

General	: In case of accident or if you feel unwell, seek medical advice immediately (show safety data sheet if possible).
After inhalation	: Take victim to fresh air, in a quiet place and if necessary take medical advice.
After skin contact	: After contact with skin, take off immediately all contaminated clothing, and wash immediately with plenty of water and soap.
After eye contact	: Wash immediately with lots of water.
After ingestion	: If swallowed, do not induce vomiting: seek medical advice immediately and show this container label.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries	: In case of accident or if you feel unwell, seek medical advice immediately (show this label if possible).
-------------------	---

4.3. Indication of any immediate medical attention and special treatment needed

First Aid, decontamination, treatment of symptoms.

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

Suitable extinguishing media	: powder, alcohol-resistant foam, water spray, carbon dioxide.
Unsuitable extinguishing media	: Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard	: Although this substance has flammability data, it is difficult to ignite in air and is classified as non-flammable.
-------------	---

5.3. Advice for firefighters

Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection.
Other information	: Use water spray/stream to protect personnel and to cool endangered containers.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Keep away from sources of ignition - No smoking.
------------------	--

Motor Oil 10W-40 Premium Longdrain Plus

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

6.1.1. For non-emergency personnel

Protective equipment : Wear suitable protective clothing and eye/face protection.

6.1.2. For emergency responders

Protective equipment : Wear respiratory protection. Wear suitable protective clothing and gloves.

6.2. Environmental precautions

Avoid release to the environment. Prevent spreading over great surfaces (e.g. by damming or installing oil booms). Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

For containment : Prevent spreading over great surfaces (e.g. by damming or installing oil booms).

Methods for cleaning up : Clean up with absorbent material (for example sand, sawdust, neutral absorbent granule, silica gel).

Other information : Can be slippery on hard, smooth walking area.

6.4. Reference to other sections

Information on disposal - see Section 13. Information on personal protective equipment - see Chapter 8. Information on safe handling - see Section 7.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Remove all sources of ignition.

Handling temperature : < 40 °C

Hygiene measures : When using do not eat, drink or smoke. Wash hands before breaks and at the end of work.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Provide for sufficient ventilation and punctiform suction at critical points.

Storage conditions : Store in original container.

Incompatible products : Do not use with strong oxidizing agents, nor with strong acids or strong bases.

Storage temperature : < 40 °C

Storage area : Ensure adequate ventilation of the storage area. Keep container tightly closed and dry.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Additional information : Based on ACGIH TLV, a concentration of 5 mg/m³ oilspray (TWA, 8 hour workday) is recommended.

8.2. Exposure controls

Technical measures:

If suction of the immediate vicinity is impossible or insufficient, adequate airing of the working place must be ensured.

Personal protective equipment:

Gloves. Safety glasses.

Materials for protective clothing:

Suitable material: neoprene. nitrile rubber

Hand protection:

Wear suitable gloves.

Eye protection:

Safety glasses

Skin and body protection:

No special clothing/skin protection equipment is recommended under normal conditions of use

Respiratory protection:

Not necessary with sufficient ventilation

Motor Oil 10W-40 Premium Longdrain Plus

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830



SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Oily.
Colour	: Yellowbrown.
Odour	: characteristic.
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: > 200 °C
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Density	: 864 g/l
Solubility	: Slightly soluble, the product remains on the water surface. Water: practically insoluble
Log Pow	: No data available
Viscosity, kinematic	: 88 mm ² /s
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

None under normal use.

10.2. Chemical stability

The product is stable at normal handling- and storage conditions.

10.3. Possibility of hazardous reactions

No additional information available

10.4. Conditions to avoid

None under normal use.

10.5. Incompatible materials

Oxidizing substances. Acids and bases.

10.6. Hazardous decomposition products

On burning: release of harmful/irritant gases/vapours e.g.: carbon monoxide - carbon dioxide.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

Motor Oil 10W-40 Premium Longdrain Plus

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Distillates (petroleum), solvent-dewaxed heavy paraffinic, Baseoil - unspecified, [A complex combination of hydrocarbons obtained by removal of normal paraffins from a petroleum fraction by solvent crystallization. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity not less than 100 SUS at 100 °F (19cSt at 40 °C).] (64742-65-0)

LD50 oral	> 5000 mg/kg
LD50 dermal rabbit	> 5000 mg/kg
LC50 inhalation rat (mg/l)	5,53 mg/l/4h

Reaction products of benzeneamine, N-phenyl- with nonene (branched) (36878-20-3)

LD50 oral rat	> 5000 mg/kg (OECD 401 method)
LD50 dermal rat	> 2000 mg/kg (OECD 402 method)

reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate (125643-61-0)

LD50 oral rat	> 2000 mg/kg (OECD 401 method)
LD50 dermal rat	> 2000 mg/kg (OECD 402 method)

Zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate)

LD50 oral rat	2600 mg/kg
LD50 dermal rat	> 3160 mg/kg OECD 402

Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified

Distillates (petroleum), solvent-dewaxed heavy paraffinic, Baseoil - unspecified, [A complex combination of hydrocarbons obtained by removal of normal paraffins from a petroleum fraction by solvent crystallization. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity not less than 100 SUS at 100 °F (19cSt at 40 °C).] (64742-65-0)

LOAEL (oral, rat, 90 days)	125 mg/kg bodyweight/day
NOAEL (inhalation, rat, dust/mist/fume, 90 days)	> 980 mg/l/6h/day
NOAEL (subchronic, oral, animal/male, 90 days)	>= 2000 mg/kg bodyweight
NOAEL (subchronic, oral, animal/female, 90 days)	>= 2000 mg/kg bodyweight

Aspiration hazard	: Not classified
-------------------	------------------

Motor Oil 10W-40 Premium Longdrain Plus

Viscosity, kinematic	88 mm ² /s
----------------------	-----------------------

SECTION 12: Ecological information

12.1. Toxicity

Reaction products of benzeneamine, N-phenyl- with nonene (branched) (36878-20-3)

LC50 fish 1	> 100 mg/l @ 96h
LC50 other aquatic organisms 1	600 mg/l @ 72h (Algea)
EC50 Daphnia 1	51 mg/l @ 48h
EC50 72h algae (1)	> 100 mg/l
NOEC chronic algae	33 mg/l @ 96h

reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate (125643-61-0)

LC50 fish 1	> 74 mg/l @96h
LC50 fish 2	> 100 mg/l @ 14d
EC50 Daphnia 1	4,3 mg/l @ 24 h
EC50 Daphnia 2	> 100 mg/l @ 48 h
NOEC chronic fish	0,001 mg/l @ 36 d
NOEC chronic algae	>= 3 mg/l @ 72 h

Zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate)

LC50 fish 1	4,5 ml/l OECD 203 (Oncorhynchys mykiss) 96h
LC50 other aquatic organisms 1	2,1 ppm OECD 201 (Selenastrum capricornutum) 48h
EC50 Daphnia 1	5,4 ml/l OECD 202 (Daphnia magna) 48h

Motor Oil 10W-40 Premium Longdrain Plus

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

12.2. Persistence and degradability

Reaction products of benzeneamine, N-phenyl- with nonene (branched) (36878-20-3)	
Persistence and degradability	Poorly biodegradable.
Biodegradation	0 % Sturm-test @28d
reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate (125643-61-0)	
Persistence and degradability	Poorly biodegradable.
Biodegradation	1 % @28 d
Zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate)	
Biodegradation	1,5 % OECD 301B 28d

12.3. Bioaccumulative potential

Distillates (petroleum), solvent-dewaxed heavy paraffinic, Baseoil - unspecified, [A complex combination of hydrocarbons obtained by removal of normal paraffins from a petroleum fraction by solvent crystallization. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity not less than 100 SUS at 100 °F (19cSt at 40 °C).] (64742-65-0)	
Log Pow	> 3
Reaction products of benzeneamine, N-phenyl- with nonene (branched) (36878-20-3)	
Bioconcentration factor (BCF REACH)	1730
Log Kow	3,6 @0.1d
Bioaccumulative potential	Moderate bioconcentration.
reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate (125643-61-0)	
Bioconcentration factor (BCF REACH)	258 (OECD 305 method)
Log Pow	9,2
Bioaccumulative potential	Moderately bioaccumulative.
Zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate)	
Log Pow	0,9 @23C

12.4. Mobility in soil

Reaction products of benzeneamine, N-phenyl- with nonene (branched) (36878-20-3)	
Log Koc	> 2000
Soil	Low mobility (soil).
reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate (125643-61-0)	
Log Koc	> 2000
Soil	Low mobility (soil).

12.5. Results of PBT and vPvB assessment

Component	
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based (72623-87-1)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
Reaction products of benzeneamine, N-phenyl- with nonene (branched) (36878-20-3)	This substance does not meet the PBT/vPvB criteria of REACH, annex XIII.
reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate (125643-61-0)	This substance does not meet the PBT/vPvB criteria of REACH, annex XIII.

12.6. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Regional legislation (waste)	: Waste disposal according to official state regulations.
Waste materials	: After use, this oil must be sent to a used oil collecting location. Incorrect disposal of used oil endangers the environment. Every mixture with foreign substances such as solvents, brake- and cooling liquids is forbidden. Used oil is hazardous waste.
European List of Waste (LoW) code	: 13 02 00 - Waste engine, gear and lubricating oils. 13 02 05- Mineral-based non-chlorinated engine, gear and lubricating oils. 15 01 10 Packaging containing residues of or contaminated by dangerous substances.

Motor Oil 10W-40 Premium Longdrain Plus

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

ADR	IMDG
14.1. UN number	
Not applicable	Not applicable
14.2. UN proper shipping name	
Not applicable	Not applicable
14.3. Transport hazard class(es)	
Not applicable	Not applicable
Not applicable	Not applicable
14.4. Packing group	
Not applicable	Not applicable
14.5. Environmental hazards	
Dangerous for the environment : No	Dangerous for the environment : No Marine pollutant : No
No supplementary information available	

14.6. Special precautions for user

- Overland transport

No data available

- Transport by sea

No data available

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No additional information available

SECTION 16: Other information

Full text of H- and EUH-statements:

Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Aquatic Chronic 4	Hazardous to the aquatic environment — Chronic Hazard, Category 4
Asp. Tox. 1	Aspiration hazard, Category 1
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Sensitisation — Skin, Category 1
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H411	Toxic to aquatic life with long lasting effects
H413	May cause long lasting harmful effects to aquatic life.
EUH208	Contains . May produce an allergic reaction.
EUH210	Safety data sheet available on request.

Motor Oil 10W-40 Premium Longdrain Plus

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product