



53000 2-Stroke Gear Oil Semi Synthetic 10W-40

Document version: November 18th 2018



Description

This gear oil is suitable for all 2-stroke motorcycles gearboxes with or without a clutch. The MPM 2-stroke gear oil provides easy gear shifting and can be used in case the recommendation is SAE 10W-30 or SAE 10W-40.

According to the specifications of

API SL
JASO MA / MA2

Packing units

| ART. NO. | VOLUME | ITEMS PER UNIT | ITEMS PER PALLET |
|----------|--------|----------------|------------------|
| 53001 | 1 L | 6 | 450 |
| 53020 | 20 L | 1 | 30 |
| 53060 | 60 L | 1 | 12 |
| 53205 | 205 L | 1 | 2 |
| 53999 | 1000 L | 1 | - |
| P53000 | bulk | 1 | - |

Typical characteristics

| TEST | VALUE | |
|------------------------------|-------------|--------------------|
| SAE | 10W-40 | |
| Density at 15°C | 0,876 | kg/l |
| Colour | Yellowbrown | |
| Kinematic viscosity at 40°C | 91 | mm ² /s |
| Kinematic viscosity at 100°C | 14,1 | mm ² /s |
| Viscosity index | 160 | |
| Flashpoint COC | 224 | °C |
| Pourpoint | -39 | °C |
| Total Base number | 6,6 | mgKOH/g |