



57000 4-Stroke Motorcycle Oil 5W-40 Premium Synthetic

Document version: November 18th 2018



Description

This 4-stroke fully synthetic SAE 5W-40 motorcycle engine oil has been specially manufactured for the latest generation of motorcycles and scooters. This exceptional anti-wear / anti-friction additive blend enhances performance, and the high lubricity properties of the product also extends engine lifetime. It is suitable for the lubrication of gearboxes with or without wet clutches.

According to the specifications of

API SL
JASO MA / MA2

Packing units

| ART. NO. | VOLUME | ITEMS PER UNIT | ITEMS PER PALLET |
|----------|--------|----------------|------------------|
| 57001 | 1 L | 6 | 450 |
| 57020 | 20 L | 1 | 30 |
| 57060 | 60 L | 1 | 12 |
| 57205 | 205 L | 1 | 2 |
| P57000 | bulk | 1 | - |

Typical characteristics

| TEST | VALUE | |
|------------------------------|-------|--------------------|
| SAE | 5W-40 | |
| Density at 15°C | 0,852 | kg/l |
| Colour | amber | |
| Kinematic viscosity at 40°C | 80 | mm ² /s |
| Kinematic viscosity at 100°C | 14,1 | mm ² /s |
| Viscosity index | 183 | |
| Flashpoint COC | 230 | °C |
| Pourpoint | -42 | °C |
| Total Base number | 6,6 | mgKOH/g |