



## AD25000 Radiator Flush

Document version: November 17th 2018



### Description

MPM radiator flush is used to completely clean and remove any contamination within the entire cooling system.

#### Main benefits

- Superior cleaning agents clean and flush the entire cooling system.
- Removes sludge, rust and other deposits.
- Prevents build-up of acid contamination.
- Does not harm rubber hoses, metal parts and gaskets.
- Is not poisonous and does not contain acids.

#### Application

Suitable for all petrol, diesel and LPG engines cooling systems with radiators made of aluminum, plastic or steel.

Mixable with water, cooling fluids and conventional anti-freeze.

#### Appliance instruction

- Shake well before use.
- Add contents of one 250ml bottle to the cooling system then drive for approximately 30 minutes and finally drain the cooling system.
- Flush with water and refill the cooling system with the OEM recommended fluid specification as per manufacturer's requirements.
- The contents of one 250ml bottle is suitable to treat cooling systems up to 12 litres.

Attention: Be careful whilst opening or draining the radiator / cooling system as hot coolant or steam may escape / vent from the system.

### Packing units

ART. NO.	VOLUME	ITEMS PER UNIT	ITEMS PER PALLET
AD25250	0.25 L	6	1548
AD25999	1000 L	1	-

### Typical characteristics

TEST	VALUE	
Density at 20°C	1,0	kg/l
Colour	blank	
Odour	neutral	
PH	9,5 - 10,5	