



# PTFE Spray Aerosol

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Date of issue:

Revision date: 01/04/2014

:

version: 18.0

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Mixture  
 Product name : PTFE Spray Aerosol  
 Product code : A204  
 Vaporizer : Aerosol

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### 1.2.1. Relevant identified uses

Main use category : Professional use  
 Use of the substance/mixture : This PTFE-spray is a PTFE-based water-repellent lubricant and protection product for use in almost all industrial sectors, with a temperature resistance from -50°C to +210°C. MPM PTFE Spray can be used as a lubricant on sliding surfaces, guides, wires, cutting tools, pulleys, conveyor belts, gears, joints and pawls. MPM PTFE Spray can also be used for guides of sliding roofs, locks and hinges in industry and the automotive and shipbuilding sectors.

##### 1.2.2. Uses advised against

No additional information available

#### 1.3. Details of the supplier of the safety data sheet

MPM International Oil Company  
 Cyclotronweg 1  
 2629 HN Delft - Nederland  
 T +31 (0)15 2514030 - F +31 (0)15 2514031  
[info@mpmoil.nl](mailto:info@mpmoil.nl) - [www.mpmoil.nl](http://www.mpmoil.nl)

#### 1.4. Emergency telephone number

Emergency number : +31 (0)15 2514030 (08.00 - 17.00)

Country	Official advisory body	Address	Emergency number
Ireland	National Poisons Information Centre Beaumont Hospital	Beaumont Hospital Beaumont Road 9 Dublin	: +353 1 8379964
United Kingdom	Guy's & St Thomas' Poisons Unit Medical Toxicology Unit, Centre Hospitalier Universitaire de Constantine	Avonley Road SE14 5ER London	0870 243 2241

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Aerosol 1 H222;H229  
 Skin Irrit. 2 H315  
 STOT SE 3 H336  
 Asp. Tox. 1 H304  
 Aquatic Chronic 3 H412

Full text of hazard classes and H-statements : see section 16

#### 2.2. Label elements

##### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS02

GHS07

CLP Signal word

: Danger.

Hazardous ingredients

: Hydrocarbons, C7, n-alkanes, isoalkanes, cycloalkanes; Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cycloalkanes, <5% of n-hexane

Hazard statements (CLP)

: H222 - Extremely flammable aerosol

# PTFE Spray Aerosol

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Precautionary statements (CLP)	H229 - Pressurised container: May burst if heated
	H315 - Causes skin irritation
	H336 - May cause drowsiness or dizziness
	H412 - Harmful to aquatic life with long lasting effects
	: P101 - If medical advice is needed, have product container or label at hand
	P102 - Keep out of reach of children
	P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
	P211 - Do not spray on an open flame or other ignition source
	P251 - Do not pierce or burn, even after use
	P261 - Avoid breathing spray, vapours
	P271 - Use only outdoors or in a well-ventilated area
	P280 - Wear protective gloves
	P312 - Call a doctor, a POISON CENTER if you feel unwell
P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50°C/ 122°F	
P501 - Dispose of contents/container to officially registered waste disposal company	
P300 - Without adequate ventilation formation of explosive mixtures may be possible	

### 2.3. Other hazards

No additional information available

## SECTION 3: Composition/information on ingredients

### 3.1. Substance

Not applicable

### 3.2. Mixture

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
isobutane	(CAS No) 75-28-5 (EC no) 200-857-2 (EC index no) 601-004-00-0 (REACH-no) 01-2119485395-27	25 - 50	Flam. Gas 1, H220 Compressed gas, H280
propane	(CAS No) 74-98-6 (EC no) 200-827-9 (EC index no) 601-003-00-5 (REACH-no) 01-2119486944-21	25 - 50	Flam. Gas 1, H220 Compressed gas, H280
Hydrocarbons, C7, n-alkanes, isoalkanes, cycloalkanes	(EC no) 927-510-4 (EC index no) 01-2119475515-33-xxxx	2,5 - 10	Flam. Liq. 2, H225 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cycloalkanes, <5% of n-hexane	(EC no) 01-2119475514-35-xxxx (EC index no) 921-024-6	2,5 - 10	Flam. Liq. 2, H225 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
butane	(CAS No) 106-97-8 (EC no) 203-448-7 (EC index no) 601-004-00-0 (REACH-no) 01-2119474691-32	2,5 - 10	Flam. Gas 1, H220 Compressed gas, H280

Full text of H-statements: see section 16

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

After inhalation	: Take victim to fresh air, in a quiet place and if necessary take medical advice.
After skin contact	: After contact with skin, take off immediately all contaminated clothing, and wash immediately with plenty of water and soap.
After eye contact	: In case of contact with eyes, rinse immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Subsequently consult an ophthalmologist.
After ingestion	: Do NOT induce vomiting. Get immediate medical advice/attention.

### 4.2. Most important symptoms and effects, both acute and delayed

No additional information available

### 4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

# PTFE Spray Aerosol

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

Suitable extinguishing media : Foam. Powder. Carbon dioxide (CO<sub>2</sub>).  
Unsuitable extinguishing media : Do not use a heavy water stream.

#### 5.2. Special hazards arising from the substance or mixture

Fire hazard : May form flammable/explosive vapour-air mixture. On heating/burning: release of (highly) toxic gases/vapours e.g.: carbon monoxide - carbon dioxide.  
Explosion hazard : Vapours may form explosive mixtures with air. Heat from a fire could result in drum bursting.

#### 5.3. Advice for firefighters

Protection during firefighting : Self-contained breathing apparatus with an air line.  
Other information : Cool containers / tanks with spray water if possible. Do not allow water used to extinguish fire to enter drains or waterways.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

General measures : Keep public away. Keep away from sources of ignition - No smoking.

##### 6.1.1. For non-emergency personnel

Protective equipment : Wear suitable protective clothing and eye/face protection. Wear respiratory protection.  
Emergency procedures : Provide adequate ventilation.

##### 6.1.2. For emergency responders

Protective equipment : Wear respiratory protection. Wear suitable protective clothing and eye/face protection.

#### 6.2. Environmental precautions

Notify authorities if liquid enters sewers or public waters. Do not flush into surface water or sewer system. Avoid release to the environment.

#### 6.3. Methods and material for containment and cleaning up

For containment : Prevent spreading over great surfaces (e.g. by damming or installing oil booms).  
Methods for cleaning up : Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents).  
Other information : Ensure adequate ventilation.

#### 6.4. Reference to other sections

Information on disposal - see Section 13.

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Precautions for safe handling : If suction of the immediate vicinity is impossible or insufficient, adequate airing of the working place must be ensured. Avoid contact with skin and eyes. Take precautionary measures against static discharge. Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use. Do not spray on an open flame or other ignition source.  
Hygiene measures : When using do not eat, drink or smoke.

#### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Store in a well-ventilated place. Keep container tightly closed.  
Storage conditions : Protect from heat and direct sunlight.  
Prohibitions on mixed storage : Observe official regulations on storing packagings with pressurized containers.  
Storage area : Keep container tightly closed in a cool, well-ventilated place. Store according to local legislation.

#### 7.3. Specific end use(s)

No additional information available

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

butane (106-97-8)		
EU	IOELV TWA (mg/m <sup>3</sup> )	1430 mg/m <sup>3</sup>
EU	IOELV TWA (ppm)	600 ppm

#### 8.2. Exposure controls

Personal protective equipment : Gloves. Safety glasses.

# PTFE Spray Aerosol

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Materials for protective clothing	: Suitable material: nitrile rubber. Thickness of glove material: $\geq 0.45$ mm
Hand protection	: In the cases of special applications, it is recommended to check the chemical resistance with the manufacturer of the gloves
Eye protection	: Tightly sealed safety glasses
Skin and body protection	: Wear suitable protective clothing
Respiratory protection	: If technical suction or ventilation measures are not possible or are insufficient, protective breathing apparatus must be worn



Other information	: When using do not eat, drink or smoke. Wash hands before breaks and at the end of work. Do not breathe vapour or spray. Avoid contact with skin and eyes. Remove/Take off immediately all contaminated clothing.
-------------------	--

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Gas
Appearance	: Aerosol.
Colour	: colourless.
Odour	: Benzine.
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: Not determined.
Freezing point	: Not determined.
Boiling point	: Not determined.
Flash point	: Not applicable as aerosol.
Auto-ignition temperature	: $> 200$ °C
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Density	: 602 g/l
Solubility	: Water: not miscible Organic solvent: 92,5 %
Log Pow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: Product is not explosive. In use, may form flammable/explosive vapour-air mixture.
Oxidising properties	: No data available
Explosive limits	: No data available

### 9.2. Other information

Other properties	: Product is not explosive. Vapours may form explosive mixtures with air.
------------------	---

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No additional information available

### 10.2. Chemical stability

The product is stable at normal handling- and storage conditions.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4. Conditions to avoid

Keep cool. Protect from sunlight. Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

# PTFE Spray Aerosol

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### 10.5. Incompatible materials

No additional information available

### 10.6. Hazardous decomposition products

On burning: release of harmful/irritant gases/vapours e.g.: carbon monoxide - carbon dioxide. aldehydes.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity : Not classified

#### isobutane (75-28-5)

LC50 inhalation rat (Vapours - mg/l/4h)	> 50 mg/l/4h
---	--------------

#### propane (74-98-6)

LC50 inhalation rat (Vapours - mg/l/4h)	20 mg/l/4h
---	------------

#### Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cycloalkanes, <5% of n-hexane

LD50 oral rat	> 5840 mg/kg
---------------	--------------

LD50 dermal rat	> 2920 mg/kg
-----------------	--------------

LC50 inhalation rat (Vapours - mg/l/4h)	< 25,2 mg/l/4h
---	----------------

#### Hydrocarbons, C7, n-alkanes, isoalkanes, cycloalkanes

LD50 oral rat	> 5840 mg/kg
---------------	--------------

LD50 dermal rat	> 2920 mg/kg
-----------------	--------------

LC50 inhalation rat (Vapours - mg/l/4h)	> 23,3 mg/l/4h
---	----------------

#### butane (106-97-8)

LC50 inhalation rat (Vapours - mg/l/4h)	658 mg/l/4h
---	-------------

Skin corrosion/irritation : Causes skin irritation.  
slightly irritant but not relevant for classification

Serious eye damage/irritation : Not classified  
No irritant effect

Respiratory or skin sensitisation : Not classified

Germ cell mutagenicity : Not classified

Carcinogenicity : Not classified

Reproductive toxicity : Not classified

Specific target organ toxicity (single exposure) : May cause drowsiness or dizziness.

Specific target organ toxicity (repeated exposure) : Not classified

Aspiration hazard : May be fatal if swallowed and enters airways.

#### PTFE Spray Aerosol

Vaporizer	Aerosol
-----------	---------

Potential adverse human health effects and symptoms : Irritating. May be narcotic.

## SECTION 12: Ecological information

### 12.1. Toxicity

General : Do not release in groundwater, surfacewater or sewerage. Danger of drinking-water pollution (ground water).

Ecology - water : Harmful to aquatic organisms.

#### Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cycloalkanes, <5% of n-hexane

EC50 Daphnia 1	3 mg/l 48h
----------------	------------

#### Hydrocarbons, C7, n-alkanes, isoalkanes, cycloalkanes

EC50 Daphnia 1	3 mg/l 48h
----------------	------------

### 12.2. Persistence and degradability

No additional information available

### 12.3. Bioaccumulative potential

No additional information available

### 12.4. Mobility in soil

No additional information available

# PTFE Spray Aerosol

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### 12.5. Results of PBT and vPvB assessment

No additional information available

### 12.6. Other adverse effects

No additional information available

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Waste treatment methods	: Do not dispose of with domestic waste.
Waste disposal recommendations	: Remove to an authorized waste treatment plant.
Waste materials	: Waste disposal according to official state regulations.
European List of Waste (LoW) code	: 15 01 04 - metallic packaging 16 05 04* - gases in pressure containers (including halons) containing dangerous substances

## SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

### 14.1. UN number

UN-No.	: 1950
UN-No. (IMDG)	: 1950

### 14.2. UN proper shipping name

Proper Shipping Name (ADR)	: AEROSOLS
Proper Shipping Name (IMDG)	: AEROSOLS
Transport document description	: UN 1950 AEROSOLS, 2.1, (D)
Transport document description (IMDG)	: UN 1950 AEROSOLS, 2.1

### 14.3. Transport hazard class(es)

#### ADR

Transport hazard class(es) (ADR)	: 2.1
Danger labels (UN)	: 2.1



#### IMDG

Transport hazard class(es) (IMDG)	: 2.1
Danger labels (IMDG)	: 2.1



### 14.4. Packing group

Packing group (ADR)	: Not applicable
Packing group (IMDG)	: Not applicable

### 14.5. Environmental hazards

Dangerous for the environment	: No
Marine pollutant	: No
Other information	: No supplementary information available

### 14.6. Special precautions for user

#### - Overland transport

Classification code (ADR)	: 5F
Limited quantities (ADR)	: 11
Transport category (ADR)	: 2

# PTFE Spray Aerosol

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Tunnel restriction code (ADR) : D

### - Transport by sea

Limited quantities (IMDG) : SP277

EmS-No. (Fire) : F-D

EmS-No. (Spillage) : S-U

### 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

#### 15.1.2. National regulations

No additional information available

### 15.2. Chemical safety assessment

No additional information available

## SECTION 16: Other information

Indication of changes:

9.1	Solubility in organic solvents	Added	
9.2	VOC content	Removed	
15.1	VOC content	Removed	

Full text of H- and EUH-statements:

Aerosol 1	Aerosol, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment — Chronic Hazard, Category 3
Asp. Tox. 1	Aspiration hazard, Category 1
Compressed gas	Gases under pressure : Compressed gas
Flam. Gas 1	Flammable gases, Category 1
Flam. Liq. 2	Flammable liquids, Category 2
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
H220	Extremely flammable gas.
H222	Extremely flammable aerosol
H225	Highly flammable liquid and vapour
H229	Pressurised container: May burst if heated.
H280	Contains gas under pressure; may explode if heated
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

SDS MPM REACH

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product*