



51000A Fork Oil Light 5W

Document version: January 26th 2019



Description

This high quality SAE 5W fork oil is specially developed for use in telescopic forks and shock absorbers of road/off-road motorcycles and mopeds. This fork oil is produced with high quality mineral oils with high viscosity index. The high de-aeration properties of this MPM fork oil means that there is minimum/reduced foaming in the fork legs/shock absorber bodies. This gives optimal performance and stability not only for normal day to day use, but will maintain optimal performance under extreme road/off-road conditions. MPM SAE 5W-fork oil offers excellent protection against component wear and seal corrosion, thus resulting in increased longevity of the components. Note: Can also be used in shock-absorbers and telescopic forks of mountain bikes and bicycles where the manufacturer specifies a SAE 5W oil.

According to the specifications of

SAE 5W

Packing units

ART. NO.	VOLUME	ITEMS PER UNIT	ITEMS PER PALLET
51001A	1 L	6	450
51020A	20 L	1	30
51060A	60 L	1	12
51205A	205 L	1	2
51999A	1000 L	1	-
P51000A	bulk	1	-

Typical characteristics

TEST	VALUE	
Density at 15°C	0,859	kg/l
Colour	blue	
Kinematic viscosity at 40°C	15,4	mm ² /s
Kinematic viscosity at 100°C	3,9	mm ² /s
Viscosity index	155	
Flashpoint COC	180	°C
Pourpoint	-36	°C