



Industrial Gear Oil 460

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Revision date: 29-9-2014 version: 4.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
 Product name : Industrial Gear Oil 460
 Product code : 39000G
 Product group : Blend

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category : Professional use, Industrial use, Consumer use
 Industrial/Professional use spec : Non-dispersive use
 Used in closed systems
 Function or use category : Lubricants and additives

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

MPM International Oil Company
 Cyclotronweg 1
 2629 HN Delft - Nederland
 T +31 (0)15 2514030 - F +31 (0)15 2514031
info@mpmoil.nl - www.mpmoil.nl

1.4. Emergency telephone number

Emergency number : +31 (0)15 2514030 (08.00 - 17.00)

Country	Official advisory body	Address	Emergency number	Comment
Ireland	National Poisons Information Centre Beaumont Hospital	Beaumont Hospital Beaumont Road 9 Dublin	: +353 1 8379964	
United Kingdom	Guy's & St Thomas' Poisons Unit Medical Toxicology Unit, Centre Hospitalier Universitaire de Constantine	Avonley Road SE14 5ER London	0870 243 2241	

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Not classified

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

EUH-statements : EUH208 - Contains Long chain alkyl amine. May produce an allergic reaction
 EUH210 - Safety data sheet available on request

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Industrial Gear Oil 460

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Long chain alkyl amine		0,1 - 0,2	Acute Tox. 4 (Oral), H302 Acute Tox. 3 (Dermal), H311 Acute Tox. 2 (Inhalation), H330 Skin Corr. 1B, H314 Skin Sens. 1, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410

Full text of H-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

General	: In case of accident or if you feel unwell, seek medical advice immediately (show safety data sheet if possible).
After inhalation	: No special measures are necessary.
After skin contact	: Wash with plenty of soap and water.
After eye contact	: Wash immediately with lots of water.
After ingestion	: IF SWALLOWED: rinse mouth. Do NOT induce vomiting. Get immediate medical advice/attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries	: Not expected to present a significant hazard under anticipated conditions of normal use.
-------------------	--

4.3. Indication of any immediate medical attention and special treatment needed

First Aid, decontamination, treatment of symptoms.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: powder, alcohol-resistant foam, water spray, carbon dioxide.
Unsuitable extinguishing media	: Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

No additional information available

5.3. Advice for firefighters

Precautionary measures fire	: Do not enter fire area without proper protective equipment, including respiratory protection.
Other information	: Use water spray/stream to protect personnel and to cool endangered containers. Exercise caution when fighting any chemical fire.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Protective equipment	: Wear suitable protective clothing and eye/face protection.
----------------------	--

6.1.2. For emergency responders

Protective equipment	: Wear respiratory protection. Wear suitable protective clothing and gloves.
----------------------	--

6.2. Environmental precautions

Avoid release to the environment. Prevent spreading over great surfaces (e.g. by damming or installing oil booms). Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

For containment	: Prevent spreading over great surfaces (e.g. by damming or installing oil booms).
Methods for cleaning up	: Clean up with absorbent material (for example sand, sawdust, neutral absorbent granule, silica gel).
Other information	: Can be slippery on hard, smooth walking area.

6.4. Reference to other sections

Information on disposal - see Section 13. Information on personal protective equipment - see Chapter 8. Information on safe handling - see Section 7.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling	: Avoid all unnecessary exposure. Both local exhaust and general room ventilation are usually required.
-------------------------------	---

Industrial Gear Oil 460

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Handling temperature : < 40 °C
Hygiene measures : When using do not eat, drink or smoke. Wash hands before breaks and at the end of work.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Provide for sufficient ventilation and punctiform suction at critical points.
Storage conditions : Store in original container.
Incompatible products : Do not use with strong oxidizing agents, nor with strong acids or strong bases.
Storage temperature : < 40 °C
Storage area : Ensure adequate ventilation of the storage area. Keep container tightly closed and dry.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Industrial Gear Oil 460		
EU	IOELV TWA (mg/m ³)	5 mg/m ³

Additional information : Based on ACGIH TLV, a concentration of 5 mg/m³ oilspray (TWA, 8 hour workday) is recommended.

8.2. Exposure controls

Technical measures:

If suction of the immediate vicinity is impossible or insufficient, adequate airing of the working place must be ensured.

Personal protective equipment:

Gloves.

Materials for protective clothing:

Type of chemical protective gloves to choose depends on the concentration and quantity of dangerous substances as well as on work place specifications. Choosing the proper glove is a decision that depends not only on the type of material, but also on other quality features, which differ for each manufacturer. Suitable material: nitrile rubber. PVC (Polyvinyl chloride)

Hand protection:

Wear suitable gloves

Eye protection:

Safety glasses

Skin and body protection:

None under normal use

Respiratory protection:

Not necessary with sufficient ventilation



SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid
Appearance : Oily.
Colour : Yellowbrown.
Odour : characteristic.
Odour threshold : No data available
pH : No data available
Relative evaporation rate (butylacetate=1) : No data available
Melting point : No data available
Freezing point : -18 °C
Boiling point : No data available

Industrial Gear Oil 460

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Flash point	: 260 °C ASTM D92
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Density	: 905 g/l 15C
Solubility	: Water: practically insoluble
Log Pow	: No data available
Viscosity, kinematic	: 434 mm ² /s 40C
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

None under normal use.

10.2. Chemical stability

The product is stable at normal handling- and storage conditions.

10.3. Possibility of hazardous reactions

No additional information available

10.4. Conditions to avoid

None under normal use.

10.5. Incompatible materials

Oxidizing substances. Acids and bases.

10.6. Hazardous decomposition products

On burning: release of harmful/irritant gases/vapours e.g.: carbon monoxide - carbon dioxide.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity	: Not classified
Skin corrosion/irritation	: Not classified
Additional information	: May cause an allergic skin reaction
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified

Industrial Gear Oil 460	
Viscosity, kinematic	434 mm ² /s 40C

SECTION 12: Ecological information

12.1. Toxicity

No additional information available

Industrial Gear Oil 460

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

12.2. Persistence and degradability

Industrial Gear Oil 460

Persistence and degradability	Not soluble in water, so only minimally biodegradable.
-------------------------------	--

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Regional legislation (waste)	: Waste disposal according to official state regulations.
European List of Waste (LoW) code	: 13 02 00 - Waste engine, gear and lubricating oils. 13 02 05- Mineral-based non-chlorinated engine, gear and lubricating oils. 15 01 10 Packaging containing residues of or contaminated by dangerous substances

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

ADR	IMDG
14.1. UN number	
Not applicable	Not applicable
14.2. UN proper shipping name	
Not applicable	Not applicable
14.3. Transport hazard class(es)	
Not applicable	Not applicable
Not applicable	Not applicable
14.4. Packing group	
Not applicable	Not applicable
14.5. Environmental hazards	
Dangerous for the environment : No	Dangerous for the environment : No Marine pollutant : No
No supplementary information available	

14.6. Special precautions for user

- Overland transport

No data available

- Transport by sea

No data available

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No additional information available

Industrial Gear Oil 460

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SECTION 16: Other information

Full text of H- and EUH-statements:

Acute Tox. 2 (Inhalation)	Acute toxicity (inhal.), Category 2
Acute Tox. 3 (Dermal)	Acute toxicity (dermal), Category 3
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Acute 1	Hazardous to the aquatic environment — Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment — Chronic Hazard, Category 1
Skin Corr. 1B	Skin corrosion/irritation, Category 1B
Skin Sens. 1	Sensitisation — Skin, Category 1
H302	Harmful if swallowed.
H311	Toxic in contact with skin
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H330	Fatal if inhaled.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
EUH208	Contains . May produce an allergic reaction.
EUH210	Safety data sheet available on request.

SDS MPM REACH

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product