



# Slideway Oil 220

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Date of issue: 20-2-2012 Revision date: 8-12-2017 Supersedes: 10-2-2015 version: 6.1

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Mixture  
 Product name : Slideway Oil 220  
 Product code : 40000B  
 Product group : Blend

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### 1.2.1. Relevant identified uses

Main use category : Industrial use, Professional use, Consumer use  
 Function or use category : Lubricants and additives

##### 1.2.2. Uses advised against

No additional information available

#### 1.3. Details of the supplier of the safety data sheet

MPM International Oil Company  
 Cyclotronweg 1  
 2629 HN Delft - Nederland  
 T +31 (0)15 2514030 - F +31 (0)15 2514031  
[info@mpmoil.nl](mailto:info@mpmoil.nl) - [www.mpmoil.nl](http://www.mpmoil.nl)

#### 1.4. Emergency telephone number

Emergency number : +31 (0)15 2514030 (08.00 - 17.00 GMT+1)

Country	Official advisory body	Address	Emergency number	Comment
Ireland	National Poisons Information Centre Beaumont Hospital	Beaumont Hospital Beaumont Road 9 Dublin	: +353 1 8379964	
United Kingdom	Guy's & St Thomas' Poisons Unit Medical Toxicology Unit, Guy's & St Thomas' Hospital Trust	Avonley Road SE14 5ER London	0870 243 2241	

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Not classified

##### Adverse physicochemical, human health and environmental effects

No additional information available

#### 2.2. Label elements

##### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

EUH-statements : EUH208 - Contains Long chain alkyl acid, Long chain alkyl amine. May produce an allergic reaction.  
 EUH210 - Safety data sheet available on request.

#### 2.3. Other hazards

No additional information available

### SECTION 3: Composition/information on ingredients

#### 3.1. Substances

Not applicable

#### 3.2. Mixtures

# Slideway Oil 220

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Distillates (petroleum), solvent-dewaxed heavy paraffinic, Baseoil - unspecified, [A complex combination of hydrocarbons obtained by removal of normal paraffins from a petroleum fraction by solvent crystallization. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity not less than 100 SUS at 100 °F (19cSt at 40 °C).]	(CAS-No.) 64742-65-0 (EC-No.) 265-169-7 (EC Index-No.) 649-474-00-6	>= 0,475	Asp. Tox. 1, H304
Alkyl phosphate		0,05 - 0,15	Skin Corr. 1B, H314
Long chain alkyl acid		0,05 - 0,15	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 4, H413
Long chain alkyl amine		0,05 - 0,15	Acute Tox. 4 (Oral), H302 Acute Tox. 3 (Dermal), H311 Acute Tox. 2 (Inhalation), H330 Skin Corr. 1B, H314 Skin Sens. 1, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410

Full text of H-statements: see section 16

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

- After inhalation : Not required.
- After skin contact : Wash with plenty of soap and water.
- After eye contact : In case of contact with eyes, rinse immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart.
- After ingestion : Do NOT induce vomiting. Rinse mouth. Get immediate medical advice/attention.

#### 4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/effects : Not expected to present a significant hazard under anticipated conditions of normal use.

#### 4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

- Suitable extinguishing media : water spray, powder, foam and CO<sub>2</sub>.
- Unsuitable extinguishing media : Do not use a heavy water stream.

#### 5.2. Special hazards arising from the substance or mixture

No additional information available

#### 5.3. Advice for firefighters

- Precautionary measures fire : Do not enter fire area without proper protective equipment, including respiratory protection.
- Other information : Exercise caution when fighting any chemical fire. Use water spray/stream to protect personnel and to cool endangered containers.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

##### 6.1.1. For non-emergency personnel

- Protective equipment : Wear suitable protective clothing. Gloves.

##### 6.1.2. For emergency responders

- Protective equipment : Wear suitable protective clothing and gloves.

#### 6.2. Environmental precautions

Do not flush into surface water or sewer system. Notify authorities if liquid enters sewers or public waters.

#### 6.3. Methods and material for containment and cleaning up

- For containment : Prevent spreading over great surfaces (e.g. by damming or installing oil booms).
- Methods for cleaning up : Clean up with absorbent material (for example sand, sawdust, neutral absorbent granule, silica gel).
- Other information : Can be slippery on hard, smooth walking area.

# Slideway Oil 220

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### 6.4. Reference to other sections

No additional information available

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Precautions for safe handling : Avoid all unnecessary exposure. Both local exhaust and general room ventilation are usually required.

Handling temperature : < 40 °C

Hygiene measures : When using do not eat, drink or smoke. Wash hands before breaks and at the end of work.

### 7.2. Conditions for safe storage, including any incompatibilities

Storage temperature : < 40 °C

Storage area : Keep container tightly closed in a cool, well-ventilated place.

### 7.3. Specific end use(s)

No additional information available

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

No additional information available

### 8.2. Exposure controls

#### Personal protective equipment:

Gloves.

#### Hand protection:

Wear suitable gloves. In the cases of special applications, it is recommended to check the chemical resistance with the manufacturer of the gloves.

#### Eye protection:

Safety glasses

#### Skin and body protection:

None under normal use

#### Respiratory protection:

Not necessary with sufficient ventilation



## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state : Liquid

Appearance : Oily.

Colour : Yellowbrown.

Odour : characteristic.

Odour threshold : No data available

pH : No data available

Relative evaporation rate (butylacetate=1) : No data available

Melting point : No data available

Freezing point : No data available

Boiling point : No data available

Flash point : > 200 °C ASTM D92

Auto-ignition temperature : No data available

Decomposition temperature : No data available

Flammability (solid, gas) : No data available

Vapour pressure : No data available

Relative vapour density at 20 °C : No data available

# Slideway Oil 220

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Relative density	: No data available
Density	: 899 g/l 15C
Solubility	: Slightly soluble, the product remains on the water surface.
Log Pow	: No data available
Viscosity, kinematic	: 220 mm <sup>2</sup> /s 40C
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

### 9.2. Other information

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

None under normal use.

### 10.2. Chemical stability

The product is stable at normal handling- and storage conditions.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4. Conditions to avoid

No additional information available

### 10.5. Incompatible materials

Oxidizing substances. Acids and bases.

### 10.6. Hazardous decomposition products

None under normal conditions.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity : Not classified

**Distillates (petroleum), solvent-dewaxed heavy paraffinic, Baseoil - unspecified, [A complex combination of hydrocarbons obtained by removal of normal paraffins from a petroleum fraction by solvent crystallization. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity not less than 100 SUS at 100 °F (19cSt at 40 °C).] (64742-65-0)**

LD50 oral	> 5000 mg/kg
LD50 dermal rabbit	> 5000 mg/kg
LC50 inhalation rat (mg/l)	5,53 mg/l/4h

Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified

**Distillates (petroleum), solvent-dewaxed heavy paraffinic, Baseoil - unspecified, [A complex combination of hydrocarbons obtained by removal of normal paraffins from a petroleum fraction by solvent crystallization. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity not less than 100 SUS at 100 °F (19cSt at 40 °C).] (64742-65-0)**

LOAEL (oral, rat, 90 days)	125 mg/kg bodyweight/day
NOAEC (inhalation, rat, dust/mist/fume, 90 days)	> 980 mg/l/6h/day
NOAEL (subchronic, oral, animal/male, 90 days)	>= 2000 mg/kg bodyweight
NOAEL (subchronic, oral, animal/female, 90 days)	>= 2000 mg/kg bodyweight

Aspiration hazard : Not classified

# Slideway Oil 220

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

<b>Slideway Oil 220</b>	
Viscosity, kinematic	220 mm <sup>2</sup> /s 40C

### SECTION 12: Ecological information

#### 12.1. Toxicity

No additional information available

#### 12.2. Persistence and degradability

<b>Slideway Oil 220</b>	
Persistence and degradability	Not soluble in water, so only minimally biodegradable.

#### 12.3. Bioaccumulative potential

**Distillates (petroleum), solvent-dewaxed heavy paraffinic, Baseoil - unspecified, [A complex combination of hydrocarbons obtained by removal of normal paraffins from a petroleum fraction by solvent crystallization. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity not less than 100 SUS at 100 °F (19cSt at 40 °C).] (64742-65-0)**

Log Pow	> 3
---------	-----

#### 12.4. Mobility in soil

No additional information available

#### 12.5. Results of PBT and vPvB assessment

No additional information available

#### 12.6. Other adverse effects

No additional information available

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

Regional legislation (waste) : Waste disposal according to official state regulations.

Waste disposal recommendations : Remove to an authorized waste treatment plant.

### SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

ADR	IMDG
<b>14.1. UN number</b>	
Not applicable	Not applicable
<b>14.2. UN proper shipping name</b>	
Not applicable	Not applicable
<b>14.3. Transport hazard class(es)</b>	
Not applicable	Not applicable
Not applicable	Not applicable
<b>14.4. Packing group</b>	
Not applicable	Not applicable
<b>14.5. Environmental hazards</b>	
Dangerous for the environment : No	Dangerous for the environment : No Marine pollutant : No
No supplementary information available	

#### 14.6. Special precautions for user

##### - Overland transport

No data available

##### - Transport by sea

No data available

#### 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

### SECTION 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

##### 15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

# Slideway Oil 220

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

### 15.1.2. National regulations

No additional information available

### 15.2. Chemical safety assessment

No additional information available

## SECTION 16: Other information

Full text of H- and EUH-statements:

Acute Tox. 2 (Inhalation)	Acute toxicity (inhal.), Category 2
Acute Tox. 3 (Dermal)	Acute toxicity (dermal), Category 3
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Acute 1	Hazardous to the aquatic environment — Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment — Chronic Hazard, Category 1
Aquatic Chronic 4	Hazardous to the aquatic environment — Chronic Hazard, Category 4
Asp. Tox. 1	Aspiration hazard, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Skin Corr. 1B	Skin corrosion/irritation, Category 1B
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H413	May cause long lasting harmful effects to aquatic life.
EUH208	Contains . May produce an allergic reaction.
EUH210	Safety data sheet available on request.

SDS MPM REACH

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product*