#### **MOTOR OIL**



# Agrinol SAE 15W-40 CI-4

TS U 23.2-30802090-085:2009

According to international classification the oil comply with:

API CI-4 SAE 15W-40

#### Structure

Motor oil on a high quality mineral base. Contains additive package to ensure additional protection of vehicles powertrains.

## Область применения

**Agrinol SAE 15W-40 CI-4** is a universal motor oil on a **mineral base**.

Is intended for high speed four-stroke engines with different types of injection and turbocharging (model series from 2002). engines with EGR-exhaust gas recirculation system.

Operating temperature range: from minus 25°C to 40 °C.

### Key performance properties:

- meets rigid requirements on ecology and toxicity of exhaust gases;
- protects the engine from the formation of harmful deposits in the cylinders and at surfaces of pistons and piston rings;
- increases engine efficiency, whereby saves fuel and reduces noise;
- compatible with the materials of seals and gaskets;

#### **Features**

Euro-3, Euro-4

# Physical and chemical properties

1 Hydrodi dila diferinadi proportios		
Index name	Norm	Test methods
1 Density at 20°C, kg/m³, not more than	910	GOST 3900
2 Kinematic viscosity at 100°C, mm²/s, within	12,5-16,3	DSTU GOST 33
3 Viscosity index, not less than	120	DSTU GOST 25371
4 Open cup flash point, <sup>0</sup> C, not lower than	205	GOST 4333
5 Pour point, <sup>o</sup> C, not higher than	Minus 28	GOST 20287
6 Mass fraction of mechanical impurities, %, not more than	0,015	GOST 6370
7 Mass fraction of water, %, not more than	Traces	GOST 2477
8 Color on CNT colorimeter, CNT units, not more than	4,0	GOST 20284
9 Total Base Number, mg KOH/g, not less than	7,5	GOST 11362
10 Mass fraction of the active elements:		
- calcium, %, not less than	0,25	GOST 13538
- zinc, %, not less than	0,1	
11 Sulfated ash, %, not more than	1,5	DSTU GOST 12417
12 Stability (according to induction period of sedimentation,	Pass	GOST T 11063
30 h)	1 455	0001111000
13 Corrosion on lead plates, g/m <sup>2</sup> , not more than	10	GOST T 20502
14 Detergent properties on PZV unit, the scores, not more than	0,5	GOST 5726

**Shelf life:** 5 years from the manufacturing date.