



05000C5 Motor Oil 0W-20 Premium Synthetic C5

Document version: Feb 4, 2020



Description

This MPM premium synthetic advanced engine oil has been developed to provide excellent engine protection and improved fuel economy. Specially developed for modern turbocharged direct injection petrol engines (TGDI) to protect against Low-Speed Pre-Ignition (LSPI). Also suitable for diesel engines of passenger cars, vans and SUVs.

Specifications

ACEA C5
API SN-RC
BMW LL-17FE+
Jaguar Land Rover STJLR.51.5122
MB 229.71
Mitsubishi
Opel OV0401547

Packaging units

ART. NR.	VOLUME	ITEMS PER UNIT	ITEMS PER PALLET
05001C5	1 L	6	450
05005C5	5 L	4	112
05020C5	20 L	1	30
05060C5	60 L	1	12
05205C5	205 L	1	2
05999C5	1000 L	1	-
P05000C5	1 L	1	-

Standard analyses

TEST	VALUE	
SAE	0W-20	
Density at 15°C	0.845	kg/l
Kinematic Viscosity at 40°C	40.7	mm ² /s
Kinematic Viscosity at 100°C	8.0	mm ² /s
Viscosity Index	174	
Flashpoint COC	210	°C
Pourpoint	-57	°C
Total Base Number	7.7	mgKOH/g
Sulphated Ash	0.6	mass%

These characteristics are typical of current production. Variations in these characteristics may occur.